



Model:

SPECIAL 330 M/S 380V/60HZ/3PH

Description:

BANDSAW MACHINE WITH COMPLETE STD. ACCESSORIES

- Vertical rotation on bolt with adjustable tapered bearings without backlash.
- High-capacity band control by two-speed motor and special reducer with bronze gear tempered and ground worm screw
- Appropriately dimensioned flywheels.
- Strong band guides with tight stress-raiser bearings and adjustable width tips.
- Band stretching is obtained by electro-mechanical blade tensioner with microswitch.
- Accident-preventing devices on the flywheel casing, on the control handle, and on the blade.
- Cutting thickness 1,2 mm
- Cutting range from 45° left - 60° right
- Adjustable stop for cuts of the same size
- 0,06 kW power-driven pump for band cooling
- Operation:
Cycle start is obtained by pressing the relevant double start button. The machine performs the following operations during the cutting cycle:
 1. vice closing and activation of band motor
 2. cutting bow downstroke
 3. return of bow to initial position
 4. band motor stop
 5. vice opening.
- Possibility of manual cut



0,75 - 1,1 KW



38 - 78 M/1'



330 MM



3010 X 27 X 0,9 MM



415 KG



0°	260	250	220 x 330
45° sx	225	210	160 x 225
45° dx	215	200	160 x 210
60° dx	130	130	130 x 140

Code Reference: **MACC-0103**

Riyadh Branch

Tel.No+966 11 44 66 222
Email: trust@al-tuwaijri.com

Jeddah Branch

Tel.No +966 12 687 9999
Email: trust2@al-tuwaijri.com

Dammam Branch

Tel.No +966 13 838 8880
Email: trust3@al-tuwaijri.com