



AL-Tuwaijri

Altuwaijri Industrial Equipment co.

Model:

BORING SYSTEM 46/SPC

Description:

BORING MACHINE



TECHNICAL DETAILS

NUMBER OF VERTICAL HEADS	2
NUMBER OF SPINDLES (LEFT RED - RIGHT BLACK)	23 (11 - 12)
INTERAXIS BETWEEN SPINDLES	32 mm
INTERAXIS BETWEEN FIRST AND LAST SPINDLE	704 mm
MAX BORING DEPTH	55 mm
INSIDE DIAMETER OF QUICK CHANGE BUSHES	10 mm
MAX HEIGHT OF CLAMPS FROM WORKING TABLE	75 mm
MINIMUM DISTANCE BETWEEN THE TWO HEADS	130 mm
MAX DISTANCE BETWEEN THE TWO HEADS	650 mm
MAX DIMENSIONS OF THE WORKING PIECE	700 x 3000 mm
HEIGHT OF THE WORKING TABLE	875 mm
NUMBER OF CLAMPS	6
NUMBER OF MOTORS	2
MOTOR POWER	1,5 (1,1) HP (kW)
MOTOR R.P.M. (50 Hz)	2800 rpm
NOISE LEVEL (Max allowed 90 dB)	82 dB
WORKING AIR PRESSURE	6-8 bar
STANDARD AIR PRESSURE CONSUMPTION	20 l/ciclo-cycle
OVERAL DIMENSIONS	1160 x 1130 x 1280 mm
PACKAGE DIMENSIONS	1070 x 1220 x 1120 mm
NET/GROSS WEIGHT	370 / 410 kg

Code Reference: **MAGG-0036**

Riyadh Branch

Tel.No+966 11 44 66 222
Email: trust@al-tuwaijri.com

Jeddah Branch

Tel.No +966 12 687 9999
Email: trust2@al-tuwaijri.com

Dammam Branch

Tel.No +966 13 838 8880
Email: trust3@al-tuwaijri.com