



AL-Tuwaijri

Altuwaijri Industrial Equipment co.

Model:



2046S

Description:

DIAL INDICATOR



No.	2046S
Type	Plunger
Dial Type	Continuous
Range	10mm (1mm)
Accuracy	$\pm 13\mu\text{m}$
Graduation	0.01mm
Repeatability	5 μm
Measuring Force	1.4N or less
Graduation	$\pm 0-100$
Remarks	Lug Back



Series 2 dial indicators are Mitutoyo's most popular, and have the widest application.

- The outer clamp and lifting lever (optional) can be attached to either the right or left side. These parts can easily be installed and removed without tools.
- Secure adhesion between the bezel and crystal as well as the use of an O-ring prevents water or oil penetration.
- The spindle is made of high strength quench hardened stainless steel which resists arduous use.
- A carbide contact point is used.
- A special alloy is used for the sector gears to provide improved wear resistance.
- Application of a hard coating on the surface of the crystal makes the gauge highly scratch and chemical resistant.

Code Reference: **MIT-0668**

Riyadh Branch

Tel.No+966 11 44 66 222

Email: trust@al-tuwaijri.com

Jeddah Branch

Tel.No +966 12 687 9999

Email: trust2@al-tuwaijri.com

Dammam Branch

Tel.No +966 13 838 8880

Email: trust3@al-tuwaijri.com