



AL-Tuwaijri

Altuwaijri Industrial Equipment co.

Model:

KP-3013 (380V/60HZ/3PH)

Description:

PTP MACHINE CENTER

The KDT KP-3013 CNC machining center is designed for precise, high-speed milling processing and additive holes in various sheet and composite materials, as well as solid and soft wood. It will be useful both at the entry-level enterprise, and in large-scale production.



DISTINCTIVE FEATURES

- Processing zone 3250 * 1250 mm;
- Table type: Movable SCHMALZ traverses
- Spindle: HSD (Italy) - 13.2 kW with a cartridge HSK-63F;
- Drilling and additive group: HSD 9V + 3H + 1S;
- Servo motors for moving the portal and spindle along the X / Y / Z axes - 1.3 kW;
- Speed of movement along the X / Y / Z axes - 80/70/20 m / min;
- The mechanism of automatic tool change of a revolving type for 16 tools;
- TPA control rack in Russian (Italy) - includes: Tra WSCM - machine control;
- Tpa Cad - modeling; editing, creating control programs;
- KDT Remote Services - (tele service) remote maintenance via an Internet connection for troubleshooting, diagnostics, maintenance, repair or process optimization.
- Instrument calibration sensor;
- Dual-circuit lubrication system;
- Ability to work in the pendulum mode;
- Safety fence;

SPECIFICATIONS

Working size	3660 x 1830 x 150 mm
Max speed X/Y/Z	80/70/20 m/min
Working Area	Two Working Zone
Boring Head	9V + 3H + 1S
Spindle	13.2 kW HSK - F63
Vacuum Pump	160 M ³ /h
Total Power	35.9 kW
Overall Size	4350 x 2575 x 2535 mm
Total Magazine	16 pcs round-dbc servo tool magazine

Code Reference: **TIMW-0015**

Riyadh Branch

Tel.No+966 11 44 66 222

Email: trust@al-tuwaijri.com

Jeddah Branch

Tel.No +966 12 687 9999

Email: trust2@al-tuwaijri.com

Dammam Branch

Tel.No +966 13 838 8880

Email: trust3@al-tuwaijri.com